



US007656258B1

(12) **United States Patent**
Antaya et al.

(10) **Patent No.:** **US 7,656,258 B1**
(45) **Date of Patent:** **Feb. 2, 2010**

(54) **MAGNET STRUCTURE FOR PARTICLE ACCELERATION**

(75) Inventors: **Timothy A. Antaya**, Hampton Falls, NH (US); **Alexey L. Radovinsky**, Brookline, MA (US); **Joel H. Schultz**, Newtonville, MA (US); **Peter H. Titus**, Duxbury, MA (US); **Bradford A. Smith**, North Andover, MA (US); **Leslie Bromberg**, Sharon, MA (US)

(73) Assignee: **Massachusetts Institute of Technology**, Cambridge, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 407 days.

(21) Appl. No.: **11/463,403**

(22) Filed: **Aug. 9, 2006**

Related U.S. Application Data

(63) Continuation-in-part of application No. 11/337,179, filed on Jan. 19, 2006, now abandoned.

(60) Provisional application No. 60/760,788, filed on Jan. 20, 2006.

(51) **Int. Cl.**
H01F 6/00 (2006.01)
H01F 1/00 (2006.01)
H05H 13/00 (2006.01)

(52) **U.S. Cl.** **335/216; 313/62**
(58) **Field of Classification Search** **335/216; 313/62**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,948,384 A 2/1934 Lawrence
3,175,131 A 3/1965 Burleigh et al.

(Continued)

FOREIGN PATENT DOCUMENTS

EP 1 605 742 A1 12/2005
JP 08-264298 10/1996
SU 569 635 8/1977
WO WO-86/07229 12/1986

OTHER PUBLICATIONS

European Patent Office, International Preliminary Report on Patentability, PCT Patent Application No. US2007/001628 (Jul. 8, 2008).

(Continued)

Primary Examiner—Elvin G Enad


Assistant Examiner—Alexander Talpalatskiy

(74) *Attorney, Agent, or Firm*—Modern Times Legal; Robert J. Sayre

(57) **ABSTRACT**

A magnet structure for particle acceleration includes at least two coils that include a continuous path of superconducting material [e.g., niobium tin (Nb₃Sn) having an A15-type crystal structure] for electric current flow there through. The coils can be mounted in a bobbin, which together with the coils form a cold-mass structure. The coils are cooled to their superconducting temperatures via cryocoolers. Radial-tension members are coupled with the cold-mass structure to keep it centered, such that it remains substantially symmetrical about a central axis and is not pulled out of alignment by magnetic forces acting thereon. A wire can be wrapped around the coils, and a voltage can be applied thereto to quench the coils to prevent their operation of the coils in a partially superconducting condition, which may otherwise cause damage thereto. A magnetic yoke surrounds the cold-mass structure and includes a pair of poles that, in part, define an acceleration chamber there between. The inner surfaces of the poles have tapered profiles that establish a correct weak focusing requirement for ion and that reduce pole diameter by increasing energy gain versus radius. An integral magnetic shield is positioned about the yoke to contain magnetic fields emanating there from and can have a tortuous configuration to contain magnetic fields having a variety of orientations. The magnet structure can be very compact and can produce particularly high magnetic fields.

27 Claims, 10 Drawing Sheets



U.S. PATENT DOCUMENTS

3,868,522	A	2/1975	Bigham et al.	
3,925,676	A	12/1975	Bigham et al.	
3,958,327	A	5/1976	Marancik et al.	
4,353,033	A	10/1982	Kurasawa	
4,507,616	A	3/1985	Blosser et al.	328/234
4,589,126	A	5/1986	Augustsson et al.	378/209
4,633,125	A	12/1986	Blosser et al.	313/62
4,641,057	A	2/1987	Blosser et al.	313/62
4,641,104	A	2/1987	Blosser et al.	328/234
4,705,955	A	11/1987	Mileikowsky	250/492.1
4,726,046	A	2/1988	Nunan	378/65
4,739,173	A	4/1988	Blosser et al.	250/505.1
4,754,147	A	6/1988	Maughan et al.	250/505.1
4,771,208	A	9/1988	Jongen et al.	313/62
4,868,843	A	9/1989	Nunan	378/152
4,868,844	A	9/1989	Nunan	378/152
4,870,287	A	9/1989	Cole et al.	250/492.3
4,905,267	A	2/1990	Miller et al.	378/208
4,917,344	A	4/1990	Prechter et al.	248/664
4,968,915	A	11/1990	Wilson et al.	
4,987,309	A	1/1991	Klasen et al.	250/492.1
5,017,789	A	5/1991	Young et al.	250/396 ML
5,039,057	A	8/1991	Prechter et al.	248/664
5,072,123	A	12/1991	Johnsen	250/385.1
5,117,829	A	6/1992	Miller et al.	128/653.1
5,166,531	A	11/1992	Huntzinger	250/505.1
5,240,218	A	8/1993	Dye	248/330.1
5,260,581	A	11/1993	Lesyna et al.	250/492.3
5,382,914	A	1/1995	Hamm et al.	315/505
5,440,133	A	8/1995	Moyers et al.	250/492.3
5,511,549	A	4/1996	Legg et al.	128/653.1
5,585,642	A	12/1996	Britton et al.	250/492.3
5,668,371	A	9/1997	Deasy et al.	250/306
5,691,679	A *	11/1997	Ackermann et al.	335/216
5,778,047	A	7/1998	Mansfield et al.	378/209
5,825,845	A	10/1998	Blair et al.	378/62
5,866,912	A	2/1999	Slater et al.	250/492.1
5,895,926	A	4/1999	Britton et al.	250/492.3
6,057,655	A	5/2000	Jongen	315/502
6,107,905	A *	8/2000	Itoh et al.	335/216
6,279,579	B1	8/2001	Riazat et al.	128/897
6,323,749	B1 *	11/2001	Hsieh	335/299
6,433,336	B1	8/2002	Jongen et al.	250/305
6,621,889	B1	9/2003	Mostafavi	378/65
6,683,426	B1	1/2004	Kleeven	315/502
6,781,492	B2 *	8/2004	Takeshima et al.	335/216
6,864,770	B2 *	3/2005	Nemoto et al.	335/216
2006/0290351	A1 *	12/2006	Matsumoto	324/318

2008/0093567 A1 4/2008 Gall

OTHER PUBLICATIONS

Kim, J. W., "An Eight Tesla Superconducting Magnet for Cyclotron Studies," Ph.D. Dissertation, Michigan State University, Department of Physics and Astronomy (1994).

Wikipedia, "Cyclotron" (visited Oct. 6, 2005), <<http://en.wikipedia.org/wiki/Cyclotron>>.

Wikipedia, "Synchrotron" (visited Oct. 6, 2005), <<http://en.wikipedia.org/wiki/Synchrotron>>.

Wu, X., "Conceptual Design and Orbit Dynamics in a 250 MeV Superconducting Synchrocyclotron," Ph.D. Dissertation, Michigan State University, Department of Physics and Astronomy (1990).

C. B. Bigham, "Magnetic Trim Rods for Superconducting Cyclotrons," Nuclear Instruments and Methods (North-Holland Publishing Co.) 141 (1975) 223-228.

S. Pourrahimi, et al., "Powder Metallurgy Processed Nb3Sn(Ta) Wire for High Field NMR Magnets," IEEE Transactions on Applied Superconductivity, vol. 5, No. 2, (Jun. 1995) 1603-1606.

A. Goto, et al., "Progress on the Sector Magnets for the Riken SRC," American Institute of Physics, CP600, Cyclotrons and Their Applications 2001, Sixteenth International Conference (2001) 319-323.

D. R. Chichili, et al., "Fabrication of Nb3Sn Shell-Type Coils with Pre-Preg Ceramic Insulation," American Institute of Physics Conference Proceedings, AIP USA, No. 711 (2004—according to ISR) (XP-002436709, ISSN: 0094-243X).

WIPO, International Searching Authority (European Patent Office), International Search Report and Written Opinion for PCT/US2007/001506 (Jul. 5, 2007) (PCT application related to this US application; each of the other references cited in this IDS were cited in this Search Report and Written Opinion).

European Patent Office, International Preliminary Report on Patentability, PCT Patent Application No. US2007/001506 (May 6, 2008).

United States Patent and Trademark Office, "Office Action for U.S. Appl. No. 11/624,769", (Aug. 18, 2008).

European Patent Office, "Written Opinion of the International Preliminary Examining Authority for PCT/US2007/001506", (Feb. 18, 2008) (closest corresponding PCT application).

European Patent Office, "International Search Report and Written Opinion for PCT/US2007/001628", (Feb. 22, 2008) (another related PCT application).

Kim, J. W., et al., "Trim Coil System for the Riken Superconducting Ring Cyclotron", *Proceedings of the 1997 Particle Accelerator Conference, IEEE*, vol. 3, (1998), 3422-3424.

Gordon, M. M., et al., "Extraction Studies for a 250 MeV Superconducting Synchrocyclotron", *Proceedings of the 1987 IEEE Particle Accelerator Conference: Accelerator Engineering and Technology*, (1987), 1255-1257.

Patent Abstracts of Japan, Publication No. 08264298, "Cyclotron," (1996).

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 7




FIG. 8




FIG. 6




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 13A




FIG. 14




FIG. 15

MAGNET STRUCTURE FOR PARTICLE ACCELERATION

RELATED APPLICATIONS

This application is a continuation-in-part of U.S. patent application Ser. No. 11/337,179, filed on Jan. 19, 2006 now abandoned. This application also claims the benefit of U.S. Provisional Application No. 60/760,788, filed on Jan. 20, 2006. Each of these applications is incorporated herein by reference in its entirety.

BACKGROUND

Magnet structures that include a superconducting coil and magnetic poles have been developed for generating magnetic fields in two classes of cyclotrons (isochronous cyclotrons and synchrocyclotrons). Synchrocyclotrons, like all cyclotrons, accelerate charged particles (ions) with a high-frequency alternating voltage in an outward spiraling path from a central axis, where the ions are introduced. Synchrocyclotrons are further characterized in that the frequency of the applied electric field is adjusted as the particles are accelerated to account for relativistic increases in particle mass at increasing velocities. Synchrocyclotrons are also characterized in that they can be very compact, and their size can shrink almost cubically with increases in the magnitude of the magnetic field generated between the poles.

When the magnetic poles are magnetically saturated, a magnetic field of about 2 Tesla can be generated between the poles. The use of superconducting coils in a synchrocyclotron, however, as described in U.S. Pat. No. 4,641,057, which is incorporated herein by reference in its entirety, is reported to increase the magnetic field up to about 5 Tesla. Additional discussion of using superconducting coils in cyclotrons is provided in X. Wu, "Conceptual Design and Orbit Dynamics in a 250 MeV Superconducting Synchrocyclotron" (1990) (Ph.D. Dissertation, Michigan State University) and in J. Kim, "An Eight Tesla Superconducting Magnet for Cyclotron Studies" (1994) (Ph.D. Dissertation, Michigan State University); both of these theses are available at <http://www.nsl.msu.edu/ourlab/library/publications/index.php>, and both are incorporated herein by reference in their entirety.

SUMMARY

A magnet structure for use in an ion accelerator includes a cold-mass structure including at least two superconducting coils symmetrically positioned on opposite sides of an acceleration plane and mounted in a cold bobbin that is suspended by tensioned elements in an evacuated cryostat. Surrounding the cold-mass structure is a magnetic yoke formed, e.g., of low-carbon steel. The low-carbon steel is a ferromagnetic material and the pole magnetization strength can be at least 2 Tesla. Together, the cold-mass structure and the yoke generate a combined field in an evacuated beam chamber placed between the poles for accelerating ions. The superconducting coils generate a substantial portion of the magnetic field in the chamber (e.g., about 7 Tesla or more) when the coils are placed in a superconducting state and when a voltage is applied thereto to initiate and maintain a continuous electric current flow through the coils. The yoke is magnetized by the field generated by the superconducting coils and can contribute another 2 Tesla to the magnetic field generated in the chamber for ion acceleration.

The radius of the coils can be 20 inches or less, and the superconducting material in the coils can be Nb₃Sn, which

can be used to generate a starting magnetic field of 9.9 Tesla or greater in the pole gap for acceleration, or NbTi, which can be used to generate a starting magnetic field of 8.4 Tesla or greater in the pole gap for acceleration. In a particular embodiment, each coil is formed of an A15 Nb₃Sn type-II superconductor. The coils can be formed by winding a reacted Nb₃Sn composite conductor in a circular ring shape or in the form of a set of concentric rings. The composite conductor can be a cable of reacted Nb₃Sn wires soldered in a copper channel or the cable, alone. The cable is assembled from a predetermined number of strands of precursor tin and niobium constituents with copper and barrier materials. The wound strands are then heated to react the matrix constituents to form Nb₃Sn, wherein the niobium content in the structure increases closer to the perimeter of the cross-section of the strand.

Additionally, an electrically conductive wire coupled with a voltage source can be wrapped around each coil. The wire can then be used to "quench" the superconducting coil (i.e., to render the entire coil "normal" rather than superconducting) by applying a sufficient voltage to the wire when the coil first starts to lose its superconductivity at its inner edge during operation, thereby preserving the coil by removing the possibility of its operation with localized hot spots of high resistivity. Alternatively, stainless steel or other conductive metallic (such as copper or brass) strips can be attached to the coil perimeter or embedded in the coils, such that when a current passes through the strips, the coil is heated so as to quench the superconducting state and thereby protect the coil.

During operation, the coils can be maintained in a "dry" condition (i.e., not immersed in liquid refrigerant); rather, the coils can be cooled to a temperature below the superconductor's critical temperature by cryocoolers. Further, the cold-mass structure can be coupled with a plurality of radial tension members that serve to keep the cold-mass structure centered about the central axis in the presence and influence of the especially high magnetic fields generated during operation.

The magnetic yoke includes a pair of approximately symmetrical poles. The inner surfaces of the poles feature a unique profile, jointly defining a pole gap there between that is tapered as a function of distance from a central axis. The profile serves (1) to establish a correct weak focusing circular particle accelerator requirement for ion acceleration (via an expanding gap at increasing distances from the central axis over an inner stage) and (2) to reduce pole diameter by increasing energy gain versus radius (via a rapidly decreasing pole gap at increasing radial distances over an outer stage).

Additionally, the ion accelerator can have a suitable compact beam chamber, dee and resonator structure in which the ions are formed, captured into accelerated orbits, accelerated to final energy and then extracted for use in a number of ion-beam applications. The beam chamber, resonator and dee structure reside in an open space between the poles of the superconducting-magnet structure. The beam chamber includes provisions for ion-beam formation. The ions may be formed in an internal ion source, or may be provided by an external ion source with an ion-injection structure. The beam chamber is evacuated and serves additionally as the ground plane of the radiofrequency-accelerating structure. The RF-accelerating structure includes a dee or multiple dees, other surfaces and structures defining acceleration gaps, and means of conveying the radiofrequency waves from an external generator into the beam chamber for excitation of the dee or multiple dees.

Further still, an integral magnetic shield can be provided to surround the yoke and to contain external magnetic fields

generated there from. The integral magnetic shield can be formed of low-carbon steel (similar to the yoke) and is positioned outside the contour of a 1,000-gauss magnetic flux density that can be generated by the magnet structure during its operation. The shield can have a tortuous shape such that magnetic flux lines extending out of the yoke will intersect the integrated magnetic shield at a plurality of locations and at a plurality of angles to enable improved containment of magnetic fields having various orientations. The heads of the cryocoolers and other active elements that are sensitive to high magnetic fields are positioned outside the integral magnetic shield.

The apparatus and methods of this disclosure enable the generation of high magnetic fields from a very compact structure, thereby enabling the generation of a point-like beam (i.e., having a small spatial cross-section) of high-energy (and short-wavelength) particles. Additionally, the integral magnetic shield of this disclosure enables excellent containment of the magnetic fields generated there from. The compact structures of this disclosure can be used in particle accelerators in a wide variety of applications, wherein the accelerator can be used in a transportable form, e.g., on a cart or in a vehicle and relocated to provide a temporary source of energetic ions for diagnostic use or threat detection, such as in a security system at a port or at other types of transportation centers. The accelerator can accordingly be used at a location of need, rather than solely at a dedicated accelerator facility. Further still, the accelerator can be mounted, e.g., on a gantry for displacement of the accelerator about a fixed target (e.g., a medical patient) in a single-room system to irradiate the target with accelerated ions from the accelerator from a variety of different source positions.

BRIEF DESCRIPTION OF THE DRAWINGS

In the accompanying drawings, described below, like reference characters refer to the same or similar parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating particular principles of the methods and apparatus characterized in the Detailed Description.

FIG. 1 is a perspective sectioned diagram showing the basic structure of a high-field synchrocyclotron, omitting the coil/cryostat assembly.

FIG. 2 is a sectional illustration of the ferromagnetic material and the magnet coils for the high-field synchrocyclotron.

FIG. 3 is an illustration of a pair of iron tip rings that extend from respective pole wings and that share a common central axis of orientation, with the gap there between extended in the drawing to better facilitate illustration.

FIG. 4 is a sectional illustration of features of the high-field, split-pair superconducting coil set.

FIG. 5 is a sectional illustration of the synchrocyclotron beam chamber, accelerating dee and resonator.

FIG. 6 is a sectional illustration of the apparatus of FIG. 5, with the section taken along the longitudinal axis shown in FIG. 5.

FIG. 7 is a sectional illustration taken through the resonator conductors in the apparatus of FIG. 5 at double the scale in size.

FIG. 8 is a sectional illustration taken through the resonator outer return yoke in the apparatus of FIG. 5 at double the scale in size.

FIG. 9 shows an alternative RF configuration using two dees and axially directed RF ports.

FIG. 10 is a sectional illustration of a magnet structure, viewed in a plane in which the central axis of the magnet structure lies.

FIG. 11 is a sectional illustration of the magnet structure of FIG. 10, viewed in a plane normal to the central axis and parallel to the acceleration plane.

FIG. 12 is a sectional illustration of the cold-mass structure, including the coils and the bobbin.

FIG. 13 is a sectional illustration, showing the interior structure of a coil.

FIG. 13A is a magnified view of the section shown in FIG. 13.

FIG. 14 is a sectional illustration of an integral magnetic shield having a contorted shape.

FIG. 15 is a perspective view of a section of the integral magnetic shield of FIG. 14.

DETAILED DESCRIPTION

Many of the inventions described herein have broad applicability beyond their implementation in synchrocyclotrons (e.g., in isochronous cyclotrons and in other applications employing superconductors and/or for generating high magnetic fields) and can be readily employed in other contexts. For ease of reference, however, this description begins with an explanation of underlying principles and features in the context of a synchrocyclotron.

Synchrocyclotrons, in general, may be characterized by the charge, Q, of the ion species; by the mass, M, of the accelerated ion; by the acceleration voltage, V₀; by the final energy, E; by the final radius, R, from a central axis; and by the central field, B₀. The parameters, B₀ and R, are related to the final energy such that only one need be specified. In particular, one may characterize a synchrocyclotron by the set of parameters, Q, M, E, V₀ and B₀. The high-field superconducting synchrocyclotron of this discourse includes a number of important features and elements, which function, following the principles of synchronous acceleration, to create, accelerate and extract ions of a particular Q, M, V₀, E and B₀. In addition, when the central field alone is raised and all other key parameters held constant, it is seen that the final radius of the accelerator decreases in proportion; and the synchrocyclotron becomes more compact. This increasing overall compactness with increasing central field, B₀, can be characterized approximately by the final radius to the third power, R³, and is shown in the table below, in which a large increase in field results in a large decrease in the approximate volume of the synchrocyclotron.

B ₀ (Tesla)	R (m)	(R/R ₁) ³
1	2.28	1
3	0.76	1/27
5	0.46	1/125
7	0.33	1/343
9	0.25	1/729

The final column in the above chart represents the volume scaling, wherein R₁ is the pole radius of 2.28 m, where B₀ is 1 Tesla; and R is the corresponding radius for the central field, B₀, in each row. In this case, M=ρ_{iron} V, and E=K (R B₀)²=250 MeV, wherein V is volume.

One factor that changes significantly with this increase in central field, B₀, is the cost of the synchrocyclotron, which will decrease. Another factor that changes significantly is the portability of the synchrocyclotron; i.e., the synchrocyclotron

should be easier to relocate; for example, the synchrocyclotron can then be placed upon a gantry and moved around a patient for cancer radiotherapy, or the synchrocyclotron can be placed upon a cart or a truck for use in mobile applications, such as gateway-security-screening applications utilizing energetic beams of point-like particles. Another factor that changes with increasing field is size; i.e., all of the features and essential elements of the synchrocyclotron and the properties of the ion acceleration also decrease substantially in size with increasing field. Described herein is a manner in which the synchrocyclotron may be significantly decreased in overall size (for a fixed ion species and final energy) by raising the magnetic field using superconducting magnetic structures that generate the fields.

With increasing field, B_0 , the synchrocyclotron possesses a structure for generating the required magnetic energy for a given energy, E ; charge, Q ; mass, M ; and accelerating voltage, V_0 . This magnetic structure provides stability and protection for the superconducting elements of the structure, mitigates the large electromagnetic forces that also occur with increasing central field, B_0 , and provides cooling to the superconducting cold mass, while generating the required total magnetic field and field shape characteristic of synchronous particle acceleration.

The yoke **36**, dee **48** and resonator structure **174** of a 9.2-Tesla, 250-MeV-proton superconducting synchrocyclotron having Nb₃Sn-conductor-based superconducting coils (not shown) operating at peak fields of 11.2 Tesla are illustrated in FIG. 1. This synchrocyclotron solution was predicated by a new scaling method from the solution obtained at 5.5 Tesla in X. Wu, "Conceptual Design and Orbit Dynamics in a 250 MeV Superconducting Synchrocyclotron" (1990) (Ph.D. Dissertation, Michigan State University); it is believed that the Wu thesis provided the highest central field (B_0) level in a synchrocyclotron that had been demonstrated up to that point in time in a detailed analysis effort or experimentally in operation.

These high-field scaling rules do not require that the new ion species be the same as in the particular examples provided herein (i.e., the scaling laws are more general than just 250 MeV and protons); the charge, Q , and the mass, M , can, in fact, be different; and a scaling solution can be determined for a new species with a different Q and M . Also, the new scaled energy, E , may be different from the previous final energy. Further still, B_0 can also be changed. With each of these changes, the synchrocyclotron mode of acceleration can be preserved.

The ferromagnetic iron yoke **36** surrounds the accelerating region in which the beam chamber, dee **48** and resonator structure **174** reside; the yoke **36** also surrounds the space for the magnet cryostat, indicated by the upper-magnet cryostat cavity **118** and by the lower-magnet cryostat cavity **120**. The acceleration-system beam chamber, dee **48** and resonator structure **174** are sized for an $E=250$ MeV proton beam ($Q=1$, $M=1$) at an acceleration voltage, V_0 , of less than 20 kV. The ferromagnetic iron core and return yoke **36** is designed as a split structure to facilitate assembly and maintenance; and it has an outer radius less than 35 inches, a total height less than 40 inches, and a total mass less than 25 tons. The yoke **36** is maintained at room temperature. This particular solution can be used in any of the previous applications that have been identified as enabled by a compact, high-field superconducting synchrocyclotron, such as on a gantry, a platform, or a truck or in a fixed position at an application site.

For clarity, numerous other features of the ferromagnetic iron yoke structure **36** for high-field synchrocyclotron operation are not shown in FIG. 1. These features are now shown in

FIG. 2. The structure of the synchrocyclotron approaches 360-degree rotational symmetry about its main axis **16**, allowing for discrete ports and other discrete features at particular locations, as illustrated elsewhere herein. The synchrocyclotron also has a median acceleration plane **18**, which is the mirror-symmetry plane for the ferromagnetic yoke **36** and is the mid-plane of the split coil pair **12** and **14**; the median acceleration plane **18** also is the vertical center of the beam chamber (defined between the poles **38** and **40**), dee **48** and resonator structure **174** and of the particle trajectories during acceleration. The ferromagnetic yoke structure **36** of the high-field synchrocyclotron is composed of multiple elements. The magnet poles **38** and **40** define an upper central passage **142** and a lower central passage **144**, aligned about the central axis **16** of the synchrocyclotron, which provide access for insertion and removal of the ion source, which is positioned on the main axis **16** at the median plane **18** in the central region of the pole-gap space **46**.

A detailed magnetic field structure is utilized to provide stable acceleration of the ions. The detailed magnetic field configuration is provided by shaping of the ferromagnetic iron yoke **36**, through shaping of the upper and lower pole tip contours **122** and **124** and upper and lower pole contours **126** and **128** for initial acceleration and by shaping upper and lower pole contours **130** and **132** for high-field acceleration. These contour changes are representative only—as for each high-field-synchrocyclotron scaling solution, there may be a different number of pole taper changes to accommodate phase-stable acceleration and weak focusing; or the surfaces may also have smoothly varying contours. Ions have an average trajectory in the form of a spiral expanding along a radius, r . The ions also undergo small orthogonal oscillations around this average trajectory. These small oscillations about the average radius are known as betatron oscillations, and they define particular characteristics of accelerating ions.

The upper and lower pole wings **134** and **136** sharpen the magnetic field edge for extraction by moving the characteristic orbit resonance, which sets the final obtainable energy closer to the pole edge. The upper and lower pole wings **134** and **136** additionally serve to shield the internal acceleration field from the strong split coil pair **12** and **14**. Conventional regenerative synchrocyclotron extraction or self-extraction is accommodated by allowing additional localized pieces of ferromagnetic upper and lower iron tips **138** and **140** to be placed circumferentially around the face of the upper and lower pole wings **134** and **136** to establish a sufficient non-axi-symmetric edge field.

In particular embodiments, the iron tips **138** and **140** are separated from the respective upper and lower pole wings **134** and **136** via a gap there between; the iron tips **138** and **140** can thereby be incorporated inside the beam chamber, whereby the chamber walls pass through that gap. The iron tips **138** and **140** will still be in the magnetic circuit, though they will be separately fixed.

In other embodiments, as shown in FIG. 3, the iron tips **138** and **140** or the pole wings **134** and **136** can be non-symmetrical about the central axis **16**, with the inclusion, e.g., of slots **202** and extensions **204** to respectively decrease and increase the magnetic field at those locales. In still other embodiments, the iron tips **138** and **140** are not continuous around the circumference of the poles **38** and **40**, but rather are in the form of distinct segments separated by gaps, wherein lower local fields are generated at the gaps. In yet another embodiment, differing local fields are generated by varying the composition of the iron tips **138** and **140** or by incorporating

selected materials having distinct magnetic properties at different positions around the circumference of the tips **138** and **140**.

Multiple radial passages **154** defined in the ferromagnetic iron yoke **36** provide access across the median plane **18** of the synchrocyclotron. The median-plane passages **154** are used for beam extraction and for penetration of the resonator inner conductor **186** and resonator outer conductor **188** (see FIG. **5**). An alternative method for access to the ion-accelerating structure in the pole gap volume is through upper axial RF passage **146** and lower axial RF passage **148**.

The cold-mass structure and cryostat (not shown) include a number of penetrations for leads, cryogenics, structural supports and vacuum pumping, and these penetrations are accommodated within the ferromagnet core and yoke **36** through the upper-pole cryostat passage **150** and through the lower-pole cryostat passage **152**.

The ferromagnetic iron yoke **36** comprises a magnetic circuit that carries the magnetic flux generated by the superconducting coils **12** and **14** to the pole gap volume **46**. The magnetic circuit through the yoke **36** also provides field shaping for synchrocyclotron weak focusing at the upper pole tip **102** and at the lower pole tip **104**. The magnetic circuit also enhances the pole-gap-volume magnet field levels by containing most of the magnetic flux in the outer part of the magnetic circuit, which includes the following ferromagnetic yoke elements: upper pole root **106** with corresponding lower pole root **108**, the upper return yoke **110** with corresponding lower return yoke **112**. The ferromagnetic yoke **36** is made of a ferromagnetic substance, which, even though saturated, provides the field shaping in the pole gap **46** for acceleration.

The upper and lower magnet cryostat cavities **118** and **120** contain the upper and lower superconducting coils **12** and **14** as well as the superconducting cold-mass structure and cryostat surrounding the coils, not shown.

The location and shape of the coils **12** and **14** are also important to the scaling of a new synchrocyclotron orbit solution for a given E, Q, M and V_0 , when B_0 is significantly increased. The bottom surface **114** of the upper coil **12** faces the opposite top surface **116** of the bottom coil **14**. The upper-pole wing **134** faces the inner surface **61** of the upper coil **12**; and, similarly, the lower-pole wing **136** faces the inner surface **62** of the lower coil **14**.

Without additional shielding, the concentrated high-magnetic-field levels inside the high-field superconducting synchrocyclotron or near the external surface of the ferromagnetic yoke **36** would pose a potential hazard to personnel and equipment in nearby proximity, through magnetic attraction or magnetization effects. An integral external shields **52** of ferromagnetic material, sized for the overall external reduction in field level required, may be used to minimize the magnetic fields away from the synchrocyclotron. The shield **52** may be in the form of layers or **20** may have a convoluted surface for additional local shielding, and may have passages for synchrocyclotron services and for the final external-beam-transport system away from the cyclotron.

Synchrocyclotrons are a member of the circular class of particle accelerators. The beam theory of the circular particle accelerators is well-developed, based upon the following two key concepts: equilibrium orbits and betatron oscillations around equilibrium orbits. The principle of equilibrium orbits (EOs) can be described as follows:

- a charge of given momentum captured by a magnetic field will transcribe an orbit;
- closed orbits represent the equilibrium condition for the given charge, momentum and energy;

the field can be analyzed for its ability to carry a smooth set of EOs; and
acceleration can be viewed as transition from one EO to another.

Meanwhile, the weak-focusing principle of perturbation theory can be described as follows:

the particles oscillate about a mean trajectory (also, known as the central ray);

oscillation frequencies (v_r , v_z) characterize motion in the radial (r) and axial (z) directions respectively;

the magnet field is decomposed into coordinate field components and a field index (n); and $v_r = \sqrt{1-n}$, while $v_z = \sqrt{n}$; and

resonances between particle oscillations and the magnetic field components, particularly field error terms, determine acceleration stability and losses.

In synchrocyclotrons, the weak-focusing field index parameter, n, noted above, is defined as follows:

$$n = -\frac{r}{B} \frac{dB}{dr},$$

where r is the radius of the ion (Q, M) from the main axis **16**; and B is the magnitude of the axial magnetic field at that radius. The weak-focusing field index parameter, n, is greater than zero to enable the successful acceleration of ions to full energy in a synchrocyclotron; and the coil dominates the field index. In particular, a restoring force is provided during acceleration to keep the ions oscillating with stability about the mean trajectory. One can show that this axial restoring force exists when $n > 0$, and this requires that $dB/dr < 0$, since $B > 0$ and $r > 0$ are true. The synchrocyclotron has a field that decreases with radius to match the field index required for acceleration. Alternatively, if the field index is known, then it should be possible to specify, to some level of precision, the required electromagnetic circuit including the positions and location of many of the features, as indicated in FIG. **2**, to the level at which further detailed orbit and field computations can provide an optimized solution. With such a solution in hand, one may then attempt to scale that solution to a parameter set (B_0 , E, Q, M and V_0).

In this regard, the rotation frequency, ω , of the ions rotating in the magnetic field of the synchrocyclotron is

$$\omega = QB/\gamma M,$$

where γ is the relativistic factor for the increase in the particle mass with increasing frequency. This decreasing frequency with increasing energy in a synchrocyclotron is the basis for the synchrocyclotron acceleration mode of circular particle accelerators, and gives rise to an additional decrease in field with radius in addition to the field index change required for the axial restoring force. The voltage, V, across the gap is greater than V_{minimum} to provide phase stability; at V_{minimum} , the particles have an energy at the gap that allows them to gain more energy when crossing the next gap. Additionally, synchrocyclotron acceleration involves the principle of phase stability, which may be characterized in that the available acceleration voltage nearly always exceeds the voltage required for ion acceleration from the center of the accelerator to full energy near the outer edge. When the radius, r, of the ion decreases, the accelerating electric field must increase, suggesting that there may be a practical limit to acceleration voltages with increasing magnetic field, B.

For a given known, working, high-field synchrocyclotron parameter set, the field index, n , that may be determined from these principle effects, among others, can be used to derive the radial variation in the magnetic field for acceleration. This B versus r profile may further be parameterized by dividing the magnetic fields in the data set by the actual magnetic field value needed at full energy and also by dividing the corresponding radius values in this B versus r data set by the radius at which full energy is achieved. This normalized data set may then be used to scale to a synchrocyclotron acceleration solution at an even-higher central magnetic field, B_0 , and resulting overall accelerator compactness, if it is also at least true that (a) the acceleration harmonic number, h , is constant, wherein the harmonic number refers to the multiplier between the acceleration voltage frequency, ω_{RF} , and the ion rotation frequency, ω , in the field, as follows:

$$\omega_{RF} = h\omega;$$

and (b) the energy gain per revolution E_t is constrained such that the ratio of E_t to another factor is held constant, specifically as follows:

$$\frac{E_t}{QV_0 r^2 f(\gamma)} = const.,$$

where $f(\gamma) = \gamma^2(1 - 0.25(\gamma^2 - 1))$.

The properties of superconducting coils are further considered, below, in order to further develop a higher-field synchrocyclotron using superconducting coils. A number of different kinds of superconductors may be used in superconducting coils; and among many important factors for engineering solutions, the following three factors are often used to characterize superconductors: magnetic field, current density and temperature. B_{max} is the maximum magnetic field that may be supported in the superconducting filaments of the superconducting wire in the coils while maintaining a superconducting state at a certain useful engineering current density, J_e , and operating temperature, T_{op} . For the purpose of comparison, an operating temperature, T_{op} , of 4.5K is frequently used for superconducting coils in magnets, such as those proposed for superconducting synchrocyclotrons, particularly in the high-field superconducting synchrocyclotrons discussed herein. For the purpose of comparison, an engineering current density, J_e , of 1000 A/mm² is reasonably representative. The actual ranges of operating temperature and current densities are broader than these values.

The superconducting material, NbTi, is used in superconducting magnets and can be operated at field levels of up to 7 Tesla at 1000 A/mm² and 4.5 K, while Nb₃Sn can be operated at field levels up to approximately 11 Tesla at 1000 A/mm² and 4.5K. However, it is also possible to maintain a temperature of 2K in superconducting magnets by a process known as sub-cooling; and, in this case, the performance of NbTi would reach operating levels of about 11 Tesla at 2K and 1000 A/mm², while Nb₃Sn could reach about 15 Tesla at 2K and 1000 A/mm². In practice, one does not design magnets to operate at the field limit for superconducting stability; additionally, the field levels at the superconducting coils may be higher than those in the pole gap, so actual operating magnetic-field levels would be lower. Furthermore, detailed differences among specific members of these two conductor families would broaden this range, as would operating at a lower current density. These approximate ranges for these known properties of the superconducting elements, in addi-

tion to the orbit scaling rules presented earlier, enable selecting a particular superconducting wire and coil technology for a desired operating field level in a compact, high-field superconducting synchrocyclotron. In particular, superconducting coils made of NbTi and Nb₃Sn conductors and operating at 4.5K would span a range of operating field levels from low fields in synchrocyclotrons to fields in excess of 10 Tesla. Decreasing the operating temperature further to 2K would expand that range to operating magnetic field levels of at least 14 Tesla.

Superconducting coils are also characterized by the level of magnetic forces in the windings and by the desirability of removing the energy quickly should, for any reason, a part of the winding become normal conducting at full operating current. The removal of energy is known as a magnet quench. There are several factors related to forces and quench protection in the split coil pair **12** and **14** of a superconducting synchrocyclotron, which are addressed for a scaled high-field superconducting synchrocyclotron using a selected conductor type to operate properly; and those are shown in FIG. 4. The coil set includes a split coil pair, with upper superconducting coil **12** and lower superconducting coil **14**. The upper **12** and lower **14** superconducting coils are axially wound with alternating superconductor and insulating elements. Several types or grades of superconductor can be used, with different composition and characteristics.

Surfaces **168** in the upper superconducting coil **12** and surfaces **170** in the lower superconducting coil **14** schematically indicate boundaries where conductor grade is changed, in order to match the conductor to better the coil design. At these or other locations, additional structure may be introduced for special purposes, such as assisting quench protection or increasing the structural strength of the winding. Hence, each superconducting coil **12** and **14** can have multiple segments separated by boundaries **168** and **170**. Although three segments are illustrated in FIG. 4, this is only one embodiment, and fewer or more segments may be used.

The upper and lower coils **12** and **14** are within a low-temperature-coil mechanical containment structure referred to as the bobbin **20**. The bobbin **20** supports and contains the coils **12** and **14** in both radial and axial directions, respectively, via outer wings **17** and an inner wing **19**, as the upper and lower coils **12** and **14** have a large attractive load as well as large radial outward force. The bobbin **20** provides axial support for the coils **12** and **14** through their respective surfaces **114** and **116**. Providing access to the pole gap **46**, multiple radial passages **172** are defined in and through the bobbin **20**. In addition, multiple attachment structures (not shown) can be provided on the bobbin **20** so as to offer radial axial links for holding the coil/bobbin assembly in a proper location.

Point **156** in the upper superconducting coil **12** and point **158** in the lower superconducting coil **14** indicate approximate regions of highest magnetic field; and this field level sets the design point for the superconductor chosen, as discussed above. In addition, crossed region **164** in the upper superconducting coil **12** and crossed region **166** in the lower superconducting coil **14** indicate regions of magnetic field reversal; and in these cases, the radial force on the windings are directed inward and is to be mitigated. Regions **160** and **162** indicate zones of low magnetic field or nearly zero overall magnetic field level, and they exhibit the greatest resistance to quenching.

The compact high-field superconducting cyclotron includes elements for phase-stable acceleration, which are shown in FIGS. 5-8. FIGS. 5 and 6 provide a detailed engineering layout of one type of beam accelerating structure,

with a beam chamber 176 and resonator 174, for the 9.2 Tesla solution of FIG. 1, where the chamber 176 is located in the pole gap space. The elevation view of FIG. 5 shows only one of the dees 48 used for accelerating the ions, while the side view shows that this dee 48 is split above and below the median plane for the beam to pass within during acceleration. The dee 48 and the ions are in a volume under vacuum and defined by the beam chamber 176, which includes a beam-chamber base plate 178. The acceleration-gap-defining aperture 180 establishes the electrical ground plane. The ions are accelerated by the electric field across the acceleration gap 182 between the dee 48 and the acceleration-gap ground-plane defining aperture 180.

To establish the high fields desired across the gap 182, the dees 48 are connected to a resonator inner conductor 186 and to a resonator outer conductor 188 through dee-resonator connector 184. The outer resonator conductor 188 is connected to the cryostat 200 (shown in FIG. 9) of the high-field synchrocyclotron, a vacuum boundary maintained by the connection. The resonator frequency is varied by an RF rotating capacitor (not shown), which is connected to the accelerating dee 48 and the inner and outer conductors 186 and 198 through the resonator outer conductor return yoke 190 through the coupling port 192. The power is delivered to the RF resonant circuit through RF-transmission-line coupling port 194.

In another embodiment, an alternative structure with two dees and axial RF resonator elements is incorporated into the compact high-field superconducting synchrocyclotron, as shown schematically in FIG. 9. Such a two-dee system may allow for increased acceleration rates or reduced voltages, V_0 . Thus, two dees 48 and 49 are used; the dees 48 and 49 are separated into halves on opposite sides of the median plane and are energized by upper axial resonators 195 and 196 and by lower axial resonators 197 and 198, which are energized by external RF power sources (in addition to radial power feeds through passages 154, illustrated in FIG. 2). FIG. 9 also shows how the coil cryostat 200 is fitted into the ferromagnetic yoke structure 36.

A more complete and detailed illustration of a magnet structure 10 for particle acceleration is illustrated in FIGS. 10 and 11. The magnet structure 10 can be used, e.g., in a compact synchrocyclotron (e.g., in a synchrocyclotron that otherwise shares the features of the synchrocyclotron disclosed in U.S. Pat. No. 4,641,057), in an isochronous cyclotron, and in other types of cyclotron accelerators in which ions (such as protons, deuterons, alpha particles, and other ions) can be accelerated.

Within the broader magnetic structure, high-energy magnet fields are generated by a cold-mass structure 21, which includes the pair of circular coils 12 and 14. As shown in FIG. 12, the pair of circular coils 12 and 14 are mounted inside respective copper thermal shields 78 maintained under vacuum with intimate mechanical contact between the coils 12 and 14 and the copper thermal shields 78. Also mounted in each copper thermal shield 78 is a pressurized bladder 80 that applies a radial inward force to counter the very high hoop tension force acting on each coil 12/14 during operation. The coils 12 and 14 are symmetrically arranged about a central axis 16 equidistant above and below an acceleration plane 18 in which the ions can be accelerated. The coils 12 and 14 are separated by a sufficient distance to allow for the RF acceleration system to extend there between into the acceleration chamber 22. Each coil 12/14 includes a continuous path of conductor material that is superconducting at the designed operating temperature, generally in the range of 4-6K, but also may be operated below 2K, where additional supercon-

ducting performance and margin is available. The radius of each coil is about 17.25 inches.

As shown in FIG. 13, the coils 12 and 14 comprise superconductor cable or cable-in-channel conductor with individual cable strands 82 having a diameter of 0.6 mm and wound to provide a current carrying capacity of, e.g., between 2 million to 3 million total amps-turns. In one embodiment, where each strand 82 has a superconducting current-carrying capacity of 2,000 amperes, 1,500 windings of the strand are provided in the coil to provide a capacity of 3 million amps-turns in the coil. In general, the coil will be designed with as many windings as are needed to produce the number of amps-turns needed for a desired magnetic field level without exceeding the critical current carrying capacity of the superconducting strand. The superconducting material can be a low-temperature superconductor, such as niobium titanium (NbTi), niobium tin (Nb₃Sn), or niobium aluminum (Nb₃Al); in particular embodiments, the superconducting material is a type II superconductor—in particular, Nb₃Sn having a type A15 crystal structure. High-temperature superconductors, such as Ba₂Sr₂Ca₁Cu₂O₈, Ba₂Sr₂Ca₂Cu₃O₁₀, or YBa₂Cu₃O_{7-x}, may also be used.

The cabled strands 82 are soldered into a U-shaped copper channel 84 to form a composite conductor 86. The copper channel 84 provides mechanical support, thermal stability during quench; and a conductive pathway for the current when the superconducting material is normal (i.e., not superconducting). The composite conductor 86 is then wrapped in glass fibers and then wound in an outward overlay. Strip heaters 88 formed, e.g., of stainless steel can also be inserted between wound layers of the composite conductor 86 to provide for rapid heating when the magnet is quenched and also to provide for temperature balancing across the radial cross-section of the coil after a quench has occurred, to minimize thermal and mechanical stresses that may damage the coils. After winding, a vacuum is applied, and the wound composite conductor structure is impregnated with epoxy to form a fiber/epoxy composite filler 90 in the final coil structure. The resultant epoxy-glass composite in which the wound composite conductor 86 is embedded provides electrical insulation and mechanical rigidity. A winding insulation layer 96 formed of epoxy-impregnated glass fibers lines the interior of the copper thermal shield 78 and encircles the coil 12.

In an embodiment in which the Nb₃Sn is structured for use in a cyclotron, the coil is formed by encasing a wound strand of tin wires in a matrix of niobium powder. The wound strand and matrix are then heated to a temperature of about 650° C. for 200 hours to react the tin wires with the niobium matrix and thereby form Nb₃Sn. After such heat treatment, each Nb₃Sn strand in the cable must carry a portion of the total electric current with sufficient current margin at the operating magnetic field and temperature to maintain the superconducting state. The specification of the copper channel cross-section and epoxy composite matrix allows the high field coil to maintain its superconducting state under greater mechanical stresses that occur in such compact coils. This improved peak stress migration is also highly advantageous where the coil is operated at higher current densities to increase the magnetic field that is generated, which is accompanied by greater forces acting on the superconducting coils. Nb₃Sn conductors are brittle and may be damaged and lose some superconducting capability unless the stress state through all operations is properly limited. The wind and react method followed by the formation of an epoxy-composite mechanical structure around the windings enables these Nb₃Sn coils to be used in other applications where superconductors are used or can be

used, but where Nb₃Sn may not otherwise be suitable due to the brittleness of standard Nb₃Sn coils in previous embodiments.

The copper shields, with the coils 12 and 14 contained therein, are mounted in a bobbin 20 formed of a high-strength alloy, such as stainless steel or an austenitic nickel-chromium-iron alloy (commercially available as INCONEL 625 from Special Metals Corporation of Huntington, West Va., USA). The bobbin 20 intrudes between the coils 12 and 14, but is otherwise outside the coils 12 and 14. The top and bottom portions of the bobbin 20 (per the orientation of FIG. 12), which are outside the coils, each has a thickness (measured horizontally, per the orientation of FIG. 12) approximately equal to the thickness of the coil 12/14. The cold-mass structure 21, including the coils 12 and 14 and the bobbin 20, is encased in an insulated and evacuated stainless steel or aluminum shell 23, called a cryostat, which can be mounted inside the iron pole and yoke 36. The cold-mass structure 21 circumscribes (i.e., at least partially defines) a space for a central chamber 22 (see FIG. 11) for accelerating ions and a segment of the central axis 16 extending across the acceleration chamber 22.

As shown in FIG. 11, the magnet structure 10 also includes an electrically conducting wire 24 (e.g., in the form of a cable) encircling each coil 12/14 (e.g., in a spiral around the coil, just a small portion of which is illustrated in FIG. 11) for quenching the coil 12/14 as it goes "normal" due to increasing temperature. A voltage or current sensor is also coupled with the coils 12 and 14 to monitor for an increase in electrical resistance in either coil 12/14, which would thereby signify that a portion of the coil 12/14 is no longer superconducting.

Cryocoolers 26, which can utilize compressed helium in a Gifford-McMahon refrigeration cycle or which can be of a pulse-tube cryocooler design, are thermally coupled with the cold-mass structure 21. The coupling can be in the form of a low-temperature superconductor (e.g., NbTi) current lead in contact with the coil 12/14. The cryocoolers 26 can cool each coil 12/14 to a temperature at which it is superconducting. Accordingly, each coil 12/14 can be maintained in a dry condition (i.e., not immersed in liquid helium or other liquid refrigerant) during operation, and no liquid coolant need be provided in or about the cold-mass structure 21 either for cool-down of the cold mass or for operating of the superconducting coils 12/14.

A second pair of cryocoolers 27, which can be of the same or similar design to cryocoolers 26, are coupled with the current leads 37 and 58 to the coils 12 and 14. High-temperature current leads 37 are formed of a high-temperature superconductor, such as Ba₂Sr₂Ca₁Cu₂O₈ or Ba₂Sr₂Ca₂Cu₃O₁₀, and are cooled at one end by the cold heads 33 at the end of the first stages of the cryocoolers 27, which are at a temperature of about 80 K, and at their other end by the cold heads 35 at the end of the second stages of the cryocoolers 27, which are at a temperature of about 4.5 K. The high-temperature current leads 37 are also conductively coupled with a voltage source. Lower-temperature current leads 58 are coupled with the higher-temperature current leads 37 to provide a path for electrical current flow and also with the cold heads 35 at the end of the second stages of the cryocoolers 27 to cool the low-temperature current leads 58 to a temperature of about 4.5 K. Each of the low-temperature current leads 58 also includes a wire 92 that is attached to a respective coil 12/14; and a third wire 94, also formed of a low-temperature superconductor, couples in series the two coils 12 and 14. Each of the wires can be affixed to the bobbin 20. Accordingly, electrical current can flow from an external circuit possessing a voltage source, through a first of the high-temperature current

leads 37 to a first of the low-temperature current leads 58 and into coil 12; the electrical current can then flow through the coil 12 and then exit through the wire joining the coils 12 and 14. The electrical current then flows through the coil 14 and exits through the wire of the second low-temperature current lead 58, up through the low-temperature current lead 58, then through the second high-temperature current lead 37 and back to the voltage source.

The cryocoolers 29 and 31 allow for operation of the magnet structure away from sources of cryogenic cooling fluid, such as in isolated treatment rooms or also on moving platforms. The pair of cryocoolers 26 and 27 permit operation of the magnet structure with only one cryocooler of each pair having proper function.

At least one vacuum pump (not shown) is coupled with the acceleration chamber 22 via the resonator 28 in which a current lead for the RF accelerator electrode is also inserted. The acceleration chamber 22 is otherwise sealed, to enable the creation of a vacuum in the acceleration chamber 22.

Radial-tension links 30, 32 and 34 are coupled with the coils 12 and 14 and bobbin 20 in a configuration whereby the radial-tension links 30, 32 and 34 can provide an outward hoop force on the bobbin 20 at a plurality of points so as to place the bobbin 20 under radial outward tension and keep the coils 12 and 14 centered (i.e., substantially symmetrical) about the central axis 16. As such, the tension links 30, 32 and 34 provide radial support against magnetic de-centering forces whereby the cold mass approaching the iron on one side sees an exponentially increasing force and moves even closer to the iron. The radial-tension links 30, 32 and 34 comprise two or more elastic tension bands 64 and 70 with rounded ends joined by linear segments (e.g., in the approximate shape of a conventional race or running track) and have a right circular cross-section. The bands are formed, e.g., of spiral wound glass or carbon tape impregnated with epoxy and are designed to minimize heat transfer from the high-temperature outer frame to the low-temperature coils 12 and 14. A low-temperature band 64 extends between support peg 66 and support peg 68. The lowest-temperature support peg 66, which is coupled with the bobbin 20, is at a temperature of about 4.5 K, while the intermediate peg 68 is a temperature of about 80 K. A higher-temperature band 70 extends between the intermediate peg 68 and a high-temperature peg 72, which is at a near-ambient temperature of about 300 K. An outward force can be applied to the high-temperature peg 72 to apply additional tension at any of the tension links 30, 32 and 34 to maintain centering as various de-centering forces act on the coils 12 and 14. The pegs 66, 68, and 72 can be formed of stainless steel.

Likewise, similar tension links can be attached to the coils 12 and 14 along a vertical axis (per the orientation of FIGS. 10 and 12) to counter an axial magnetic decentering force in order to maintain the position of the coils 12,14 symmetrically about the mid-plane 18. During operation, the coils 12 and 14 will be strongly attracted to each other, though the thick bobbin 20 section between the coils 12 and 14 will counterbalance those attractive forces.

The set of radial and axial tension links support the mass of the coils 12 and 14 and bobbin 20 against gravity in addition to providing the required centering force. The tension links may be sized to allow for smooth or step-wise three-dimensional translational or rotational motion of the entire magnet structure at a prescribed rate, such as for mounting the magnet structure on a gantry, platform or car to enable moving the proton beam in a room around a fixed targeted irradiation location. Both the gravitational support and motion requirements are tension loads not in excess of the magnetic decen-

tering forces. The tension links may be sized for repetitive motion over many motion cycles and years of motion.

A magnetic yoke **36** formed of low-carbon steel surrounds the coils **12** and **14** and cryostat **23**. Pure iron may be too weak and may possess an elastic modulus that is too low; consequently, the iron can be doped with a sufficient quantity of carbon and other elements to provide adequate strength or to render it less stiff while retaining the desired magnetic levels. The yoke **36** circumscribes the same segment of the central axis **16** that is circumscribed by the coils **12** and **14** and the cryostat **23**. The radius (measured from the central axis) at the outer surfaces of the yoke **36** can be about 35 inches or less.

The yoke **36** includes a pair of poles **38** and **40** having tapered inner surfaces **42** and **44** that define a pole gap **46** between the poles **38** and **40** and across the acceleration chamber **22**. The profiles of those tapered inner surfaces **42** and **44** are a function of the position of the coils **12** and **14**. The tapered inner surfaces **42** and **44** are shaped such that the pole gap **46** (measured as shown by the reference line in FIG. **10**) expands over an inner stage defined between opposing surfaces **42** as the distance from the central axis **16** increases and decreases over an outer stage defined between opposing surfaces **44** as the distance from the central axis **16** further increases. The inner stage establishes a correct weak focusing requirement for ion (e.g., proton) acceleration when used, e.g., in a synchrocyclotron for proton acceleration, while the outer stage is configured to reduce pole diameter by increasing energy gain versus radius, which facilitates extraction of ions from the synchrocyclotron as the ions reach the perimeter of the chamber **22**.

The pole profile thus described has several important acceleration functions, namely, ion guiding at low energy in the center of the machine, capture into stable acceleration paths, acceleration, axial and radial focusing, beam quality, beam loss minimization, attainment of the final desired energy and intensity, and the positioning of the final beam location for extraction. In particular, in synchrocyclotrons, the simultaneous attainment of weak focusing and acceleration phase stability is achieved. At higher fields achieved in this magnet structure, the expansion of the pole gap over the first stage provides for sufficient weak focusing and phase stability, while the rapid closure of the gap over the outer stage is responsible for maintaining weak focusing against the deleterious effects of the strong superconducting coils, while properly positioning the full energy beam near the pole edge for extraction into the extraction channel. Where the magnetic field to be generated by the magnet is increased, the slope of the gap opening over the inner stage is greater, while the gap closing over the second stage is further diminished. Since the iron in the poles is fully magnetically saturated at pole strength above 2 Tesla, it would also be possible to accomplish this set of simultaneous objectives by substituting a nested set of superconducting coils in place of the tapered surfaces of the poles and having currents in those nested coils optimized to match the field contribution of the poles to the overall acceleration field. In addition, in another embodiment, one may replace the iron in the poles with another strong ferromagnetic material and accomplish the same results.

The iron yoke provides sufficient clearance for a beam chamber **22** containing the radiofrequency (RF) accelerator electrodes **48** (also known as "dees") formed of a conductive metal. The electrodes **48** are part of a resonator structure **174** that extends through the sides of the yoke **36** and passes through the cryostat **23** and between the coils **12** and **14**. The accelerator electrodes **48** include a pair of flat semi-circular parallel plates that are oriented parallel to and above and

below the acceleration plane **18** inside the accelerator chamber **22** (as described and illustrated in U.S. Pat. No. 4,641,057). The electrodes **48** are coupled with an RF voltage source (not shown) to accelerate emitted ions from the ion source **50** in an expanding orbital (spiral) path in the acceleration chamber **22**. Additionally, a dummy dee can be provided in the form of a planar sheet oriented in a plane of the central axis **16** (i.e., a plane that intersects the central axis in the orientation of FIG. **10** and extends orthogonally from the page) and having a slot defined therein to accommodate the acceleration plane for the particles. Alternatively, the dummy dee can have a configuration identical to that of the electrodes **48**, though the dummy dee would be coupled with an electrical ground rather than with a voltage source.

An integral magnetic shield **52** circumscribes the other components of the magnet structure **10**. The integral magnetic shield **52** can be in the form of a thin sheet (e.g., having a thickness of 2 cm) of low-carbon steel. As shown in FIG. **10**, multiple sheets can be stacked together at selected locations to provide additional shielding of sensitive areas, as is evident where the sheets are triple stacked along the sides in FIG. **10**. Alternatively, the shield **52** can have a tortuous shape (e.g., resembling a collapsed accordion structure), as shown in FIGS. **14** and **15**, and is configured such that a majority of the magnetic field generated by the coils **12** and **14** and by the yoke **36** will need to pass through the integral magnetic shield **52** at a plurality of locations and at a plurality of angles relative to the local orientation of the shield **52**. In the embodiment of FIG. **14**, the integral magnetic shield **52** has a profile wherein its orientation gradually shifts back and forth between being perpendicular to and being parallel to radial vectors **56** from the central axis **16**. Each radial vector **56** would intersect the shield **52** at two or more different locations—including at a near perpendicular angle and at a near tangential angle. At a first point of intersection **74**, where the vector **56** crosses the integral magnetic shield **52** at a near perpendicular, a normal magnetic-field component is canceled; while at a second intersection, where the vector **56** crosses the integral magnetic shield **52** at a near tangent, a tangential magnetic-field component is canceled.

The integral magnetic shield **52** is mounted at a distance from the outer surface of the magnetic yoke **36** such that it is positioned outside the contour of a 1,000-gauss magnetic-flux density generated outside the yoke **36** when a voltage is applied to the superconducting coils **12** and **14** to generate a magnetic field of 8 Tesla or more inside the acceleration chamber **22**.

The heads **29** and **31** of the cryocoolers **26** and **27** are positioned outside the integral magnetic shield **52** to shield the heads **29** and **31** from magnetic fields (which can compromise the operability of the cryocooler due to field limits in the heads **29** and **31**). Accordingly, the integral magnetic shield **52** defines respective ports therein, through which the cryocoolers **26** and **27** can be inserted.

Operation of the above-described magnet structure to generate a magnetic field for accelerating ions will now be described in the following pages.

When the magnet structure **10** is in operation, the cryocoolers **26** are used to extract heat from the superconducting coils **12** and **14** so as to drop the temperature of each below its critical temperature (at which it will exhibit superconductivity). The temperature of coils formed of low-temperature superconductors is dropped to about 4.5 K.

A voltage (e.g., sufficient to generate 2,000 A of current through the current lead in the embodiment with 1,500 windings in the coil, described above) is applied to each coil **12/14** via the current lead **58** to generate a magnetic field of at least

8 Tesla within the pole gap **46** when the coils are at 4.5 K. In particular embodiments using, e.g., Nb_3Sn , a voltage is applied to the coils **12** and **14** to generate a magnetic field of at least about 9 Tesla within the pole gap **46**. Moreover, the field can generally be increased an additional 2 Tesla by using the cryocoolers to further drop the coil temperature to 2 K. The magnetic field includes a contribution of about 2 Tesla from the fully magnetized iron poles **38** and **40**; the remainder of the magnetic field is produced by the coils **12** and **14**.

This magnet structure serves to generate a magnetic field sufficient for ion acceleration. Pulses of ions (e.g., protons) can be emitted from the ion source **50** (e.g., the ion source described and illustrated in U.S. Pat. No. 4,641,057). Free protons can be generated, e.g., by applying a voltage pulse to a cathode to cause electrons to be discharged from the cathode into hydrogen gas; wherein, protons are emitted when the electrons collide with the hydrogen molecules.

In this embodiment, The RF accelerator electrodes **48** generate a voltage difference of 20,000 Volts across the plates. The electric field generated by the RF accelerator electrodes **48** has a frequency matching that of the cyclotron orbital frequency of the ion to be accelerated. The field generated by the RF accelerator electrodes **48** oscillates at a frequency of 140 MHz when the ions are nearest the central axis **16**, and the frequency is decreased to as low as 100 MHz when the ions are furthest from the central axis **16** and nearest the perimeter of the acceleration chamber **22**. The frequency is dropped to offset the increase in mass of the proton as it is accelerated, as the alternating frequency at the electrodes **48** alternately attracts and repels the ions. As the ions are thereby accelerated in their orbit, the ions speed up and spiral outward.

When the accelerated ions reach an outer radial orbit in the acceleration chamber **22**, the ions can be drawn out of the chamber **22** (in the form of a pulsed beam) by magnetically leading them with magnets positioned about the perimeter of the chamber **22** into a linear beam-extraction passage **60** extending from the acceleration chamber **22** through the yoke **36** and then through a gap in the integral magnetic shield **52** toward, e.g., an external target. The radial tension links **30**, **32** and **34** are activated to impose an outward radial hoop force on the cold-mass structure **21** to maintain its position throughout the acceleration process.

The integral magnetic shield **52** contains the magnetic field generated by the coils **12** and **14** and poles **38** and **40** so as to reduce external hazards accompanying the attraction of, e.g., pens, paper clips and other metallic objects toward the magnet structure **10**, which would occur absent employment of the integral magnetic shield **52**. Interaction between the magnetic field lines and the integral magnetic shield **52** at various angles is highly advantageous, as both normal and tangential magnetic fields are generated by the magnet structure **10**, and the optimum shield orientation for containing each differs by 90°. This shield **52** can limit the magnitude of the magnetic field transmitted out of the yoke **36** through the shield **52** to less than 0.00002 Tesla.

When an increase in voltage or a drop in current through a coil **12/14** is detected, thereby signifying that a localized portion of the superconducting coil **12/14** is no longer superconducting, a sufficient voltage is applied to the quenching wire **24** that encircles the coil **12/14**. This voltage generates a current through the wire **24**, which thereby generates an additional magnetic field to the individual conductors in the coil **12/14**, which renders them non-superconducting (i.e., "normal") throughout. This approach solves a perceived problem in that the internal magnetic field in each superconducting coil **12/14**, during operation, will be very high (e.g., 11 Tesla) at its inner surface **62** and will drop to as low as zero at an

internal point. If a quench occurs, it will likely occur at a high-field location while a low-field location may remain cold and superconducting for an extended period. This quench generates heat in the parts of the superconductor of coils **12/14** that are normal conducting; consequently, the edge will cease to be superconducting as its temperature rises, while a central region in the coil will remain cold and superconducting. The resulting heat differential would otherwise cause destructive stresses in the coil due to differential thermal contraction. This practice of inductive quenching is intended to prevent or limit this differential and thereby enable the coils **12** and **14** to be used to generate even higher magnetic fields without being destroyed by the internal stresses. Alternatively, current may be passed through the heater strips **88** causing the heater strip temperatures to rise well above 4.5 K and thereby locally heat the superconductors to minimize the internal temperature differentials during a quench.

Cyclotrons incorporating the above-described apparatus can be utilized for a wide variety of applications including proton radiation therapy for humans; etching (e.g., micro-holes, filters and integrated circuits); radioactivation of materials for materials studies; tribology; basic-science research; security (e.g. monitoring of proton scattering while irradiating target cargo with accelerated protons); production of medical isotopes and tracers for medicine and industry; nanotechnology; advanced biology; and in a wide variety of other applications in which generation of a point-like (i.e., small spatial-distribution) beam of high-energy particles from a compact source would be useful.

In describing embodiments of the invention, specific terminology is used for the sake of clarity. For purposes of description, each specific term is intended to at least include all technical and functional equivalents that operate in a similar manner to accomplish a similar purpose. Additionally, in some instances where a particular embodiment of the invention includes a plurality of system elements or method steps, those elements or steps may be replaced with a single element or step; likewise, a single element or step may be replaced with a plurality of elements or steps that serve the same purpose. Moreover, while this invention has been shown and described with references to particular embodiments thereof, those skilled in the art will understand that various substitutions and alterations in form and details may be made therein without departing from the scope of the invention; further still, other aspects, functions and advantages are also within the scope of the invention. The appropriate components, processes, and methods of all references incorporated by reference herein may be selected for the invention and embodiments thereof.

What is claimed is:

1. A magnet structure for use in an ion accelerator comprising:

a cold-mass structure including:

at least two coils that comprise a material that is superconducting at a nominal temperature of 4.5 K and that radially circumscribe an acceleration chamber and a segment of a central axis extending across the acceleration chamber, wherein a median acceleration plane extends orthogonally from the central axis across the acceleration chamber; and

a bobbin in which the coils are mounted, the bobbin including a pair of outer wings to support the coils in an outward radial direction and an inner wing between the coils and intersecting the median acceleration plane to support the coils in an inward axial direction;

a cryostat enclosing the cold-mass structure;

19

a dry cryocooler coupled with the cold-mass structure to cool the coils;

radial-tension links coupled with the bobbin and applying outward radial tension on the bobbin at a plurality of positions; and

a magnetic yoke wrapped around the cold-mass structure, circumscribing the segment of the central axis, and including a pair of poles having tapered inner surfaces that define a pole gap between the poles and across the acceleration chamber.

2. The magnet structure of claim 1, wherein the superconducting material is Nb₃Sn.

3. The magnet structure of claim 2, wherein the superconducting material is an A15 type-II superconductor.

4. The magnet structure of claim 2, wherein the coil comprises a composite conductor in the form of windings of:

- a wound Nb₃Sn strand; and
- a copper channel containing the wound Nb₃Sn strand, wherein the coil has a cross-section including a plurality of sections for each winding of the wound composite conductor.

5. The magnet structure of claim 4, further comprising a fiber/epoxy composite filler surrounding each section and between each section of the wound composite conductor.

6. The magnet structure of claim 1, wherein the pole gap defined by the tapered inner surfaces of the poles expands over an inner stage as the distance from the central axis increases and decreases over an outer stage as the distance from the central axis further increases.

7. The magnet structure of claim 1, wherein the coils have a radius no greater than 20 inches.

8. The magnet structure of claim 1, wherein the cryocooler is a Gifford-McMahon cryocooler or a pulse-tube cryocooler.

9. The magnet structure of claim 1, wherein the bobbin is in the form of a substantially solid block.

10. The magnet structure of claim 9, wherein the bobbin defines a radial passage in and through the bobbin.

11. The magnet structure of claim 1, wherein the wings of the bobbin are at least as thick as the coil, measured radially.

12. The magnet structure of claim 1, further comprising a pressurized bladder positioned between each coil and the bobbin to apply radial inward force on the coil.

13. The magnet structure of claim 1, wherein the radial tension links comprise elastic tension bands.

14. The magnet structure of claim 13, wherein the elastic tension bands comprise spiral-wound glass or carbon tape impregnated with epoxy.

15. A magnet structure for use in a synchrocyclotron comprising:

- a cold-mass structure including at least two superconducting coils, wherein the cold-mass structure is contained in a cryostat that circumscribes an acceleration chamber;
- a magnetic yoke wrapped around the cold-mass structure and including a pair of poles that define a pole gap between the poles and across the acceleration chamber, wherein the superconducting coils and the poles are structured to produce a radially decreasing combined magnetic field reaching at least 8 Tesla for synchrocyclotron acceleration in the acceleration chamber; and
- an integral magnetic shield surrounding the yoke in substantially all directions and positioned outside the contour of a 1,000 gauss magnetic flux density that can be generated by the magnet structure outside the yoke when

20

a voltage is applied to the superconducting coils to generate the combined magnetic field of at least 8 Tesla inside the acceleration chamber.

16. The magnet structure of claim 15, wherein the integral magnetic shield has a tortuous shape configured such that most magnetic field lines extending from the magnetic yoke will intersect the integral magnetic shield at a plurality of locations and at a plurality of angles.

17. The magnet structure of claim 15, wherein the integral magnetic shield comprises iron.

18. The magnet structure of claim 15, further comprising a cryocooler coupled with the cold-mass structure to cool the coils.

19. The magnet structure of claim 18, wherein the cryocooler includes a head that is positioned outside the boundary of the integral magnetic shield.

20. A method for generating a magnetic field for ion acceleration comprising:

- providing a cold-mass structure in a cryostat that circumscribes an acceleration chamber, the cold-mass structure including at least two superconducting coils centered about a central axis, a cryocooler coupled with the cold-mass structure; a magnetic yoke positioned about the cold-mass structure and including a pair of poles that define a tapered pole gap there between and across the acceleration chamber;
- cooling the superconducting coils to or below the critical temperature of the superconductor and applying a voltage to the cold-mass structure to generate a magnetic field of at least 8 Tesla within the pole gap; and
- injecting an ion into the acceleration chamber and accelerating the ion in an outward spiral in the acceleration chamber, wherein the ion is subjected to a radially decreasing magnetic field in the acceleration chamber as it is accelerated outward, and wherein a weak-focusing field index parameter, n , is in the range from 0 to 1 across the entire span of the spiral traversed by the ion, where $n = -(r/B)(dB/dr)$, and where B is the magnetic field, and r is the radius from the central axis.

21. The method of claim 20, wherein the superconducting coils comprise Nb₃Sn.

22. The method of claim 21, wherein a magnetic field of at least 9.9 Tesla is generated in the pole gap.

23. The method of claim 20, wherein radial-tension links are coupled with the cold-mass structure, the method further comprising applying an outward radial force on the cold-mass structure to maintain the positioning of the cold-mass structure.

24. The method of claim 23, wherein an integral magnetic shield is provided about the yoke at a distance outside the contour of a 1,000 gauss magnetic flux density generated by the cold-mass structure and by the magnetic yoke.

25. The method of claim 20, wherein the pole gap increases over an inner stage as the distance from the central axis increases, and wherein the pole gap decreases over an outer stage as the distance from the central axis further increases.

26. The method of claim 20, wherein the cold-mass structure and yoke generate a magnetic field of at least about 9 Tesla within the acceleration chamber.

27. The method of claim 20, wherein the coils are maintained in a dry state in the cold-mass structure when the magnetic field is generated.

* * * * *